

NOTES:

- EXCAVATE TRENCHES TO PROPER WIDTH, AND PROPER DEPTH AS REQUIRED BY STATE AND LOCAL CODES.
- SURFACE IS REQUIRED. SMOOTH IRREGULARITIES IN THE EXCAVATION. A LEVEL, FLAT
- 3. ASSEMBLE BIODIFFUSER LEACHING CHAMBERS AND UNIVERSAL **ENDPLATES TOGETHER IN TRENCH(ES).**
- 4. INSTALL UNIVERSAL END CAP AND SECURE IN PLACE WITH BACKFILL
- 5. PUNCH OUT PIPE HOLE OPENINGS IN THE END PLATES AS NEEDED AND CONNECT INLET PIPES

- 6 CLAY, SILT, OR DEBRIS SHALL BE INCLUDED.) FILL SIDEWALL AREA TO TOP CHAMBERS WITH NATIVE SOIL (COARSE SAND OR FINE GRAVEL, MAY ALSO BE USED: NO HEAVY
- "WALK IN" FILL TO COMPACT SOIL ALONG SIDES OF BIODIFFUSER THIS IS VERY IMPORTANT TO ACHIEVE LOAD RATING
- LARGE ROCKS OR DEBRIS IN COVER MATERIAL. COVER HEIGHTS AND LIVE FOR MAXIMUM FILL HEIGHTS. GRANULAR COVER AFTER CONSOLIDATION FOR H-10 APPLICATIONS. AVOID REQUIREMENTS. CONTACT ADS WHEN POOR SOILS ARE ENCOUNTERED AND LOADING LIMITS ARE IMPACTED BY BOTH SOIL TYPE AND COMPACTION COVER BIODIFFUSER LEACHING CHAMBERS TO A MINIMUM OF 12" OF

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE MATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE MATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT. 1, " STANDARD BIODIFFUSER
TRENCH INSTALLATION REV. MODIFY LAYOUT DESCRIPTION CKS ВΥ MM/DD/YY 6/27/07 4640 TRUEMAN BLVD HILLIARD, OHIO 43026 CHK'D ME QUD SELVIC KAH

DRAWING NUMBER:

STD-910A

DVANCED

11/1/04 STN